UPLOAD DATA IN REAL TIME VIA WIFI WITHOUT A COMPUTER

LTI-WM-WiFi LogTag WiFi Interface Cradle

The new LogTag Wall Mounted Wireless Interface Cradle is a high-speed interface device that connects TREX/TREL/TRED data loggers to your WiFi network for real-time data download to a cloud platform.

- Use LTI-WM-WiFi to upload data in real time without access to a computer and installed software.
- Accepts TREX/TREL/TRED data loggers.
- Easily set up to work with your WiFi network.

S/N: A0B5000001TT

LogTag[®] REAL TIME WIFE

- Downloaded data is fully encrypted and automatically uploaded to a secure server.
- Uploaded data is immediately available to authorized stakeholders.
- If the WiFi network is temporarily unavailable, downloaded data is stored in the LTI-WM- WiFi's buffer memory.
- Robust and reliable contacts are good for thousands of insertions.
- Inbuilt indicators show data download and network access status.

LogTag Recorders

New Tab × \				×
LogTag [®] Online				Hello, Ben 🔻
Dashboard				
Locations for: Ben		Recently Uploaded F	iles (View all)	
	Ward A Vaccine Refrigerator	File Name	Device Name	Time Uploaded
	VFC Vaccine Refrigerator set to 5°C	TRIX-8: 90000061271	2 Started Kitchen Fridge	10:45am - 23/03/18
	Temperature 7°C			
⚠ High Alarm Triggered!	REVIEW			
		Recently Registered Devices (View all)		Register a Device
		Device Name	Serial Number Model	Last Connection
		Kitchen Fridge	9000006127 TRIX-8	10:45am - 23/03/18
		Kitchen Freezer	A90000061271 UTRED30-WiFi	
	Dashboard Locations Devices	LogTag Drive		

Receive real-time notifications with LogTag Online

LogTag Online is a secure, cloud-based application for managing & sharing your temperature data via a role-based permission system. A wide range of features include: real-time alarm notifications, location monitoring, temperature logs and troubleshooting records. No installed software is required and LogTag Online is accessible via any Internet-enabled device.

Specifications

Product Model	LTI-WM-WiFi
Operating Temperature Range	-25°C to +40°C
Storage Temperature Range	-40°C to +70°C
USB Standard	2.0
Logger buffer	Up to 45 logger downloads can be buffered
WiFi	2.4GHz 802.11 b/g/n High sensitivity internal antenna
Network Security	WPA/WPA2-PSK
Environmental	IP50 (Rated for inside use only)
Power Source	5V (Computer or USB wall charger)
Size	(W)70mm (H)114mm (D)38mm
Weight	100g
Case Material	ABS
Connectors	USB Micro
Certifications	FCC, CE & RoHS Compliant
Range (Clear Line of Sight)	40m
Accessories	2.0m USB cable